

SAFETY DATA SHEET



Gasoline 98 (E5)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Gasoline 98 (E5)
Viscosity or Type : EN 228 Euro 98, E5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Unleaded fuel for gasoline engines

Identified uses
<input checked="" type="checkbox"/> Distribution of substance Use in fuel - Consumer

1.3 Details of the supplier of the safety data sheet

Manufacturer / Distributor : Kuwait Petroleum (Belgium) N.V.
Brusselstraat 59 - Bus 1
2018, Antwerp, Belgium
Tel. +32 3 241 33 00, Fax +32 3 241 35 31

e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Netherlands : +31 10 713 8195
Europe : +44 (0) 1235 239 670
Global (English only) : +44 (0) 1865 407 333



National advisory body/Poison Center

Telephone number : Nationaal Vergiftigingen Informatie Centrum, Utrecht +31 (0)30 274 8888 (Only for the purpose of informing medical personnel in cases of acute intoxications.)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

<input checked="" type="checkbox"/> FLAMMABLE LIQUIDS	Category 1	H224
SKIN CORROSION/IRRITATION	Category 2	H315
GERM CELL MUTAGENICITY	Category 1B	H340
CARCINOGENICITY	Category 1A	H350
TOXIC TO REPRODUCTION	Category 2	H361
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)	Category 3	H336
ASPIRATION HAZARD	Category 1	H304
AQUATIC HAZARD (LONG-TERM)	Category 2	H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : None.

Ingredients of unknown ecotoxicity : None.

SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H224 - Extremely flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H340 - May cause genetic defects.
H350 - May cause cancer.
H361 - Suspected of damaging fertility or the unborn child.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

General

: P103 - Read label before use.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention

: P201 - Obtain special instructions before use.
P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapor.
P264 - Wash thoroughly after handling.

Response

: P391 - Collect spillage.
P308 + P313 - IF exposed or concerned: Get medical advice or attention.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage

: P405 - Store locked up.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Keep cool.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

: Gasoline
toluene
benzene

Supplemental label elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Yes, applicable.

Tactile warning of danger

: Yes, applicable.

Gasoline 98 (E5)

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type	Notes
Gasoline	REACH #: 01-2119471335-39, 01-2119489270-37 EC: 289-220-8 CAS: 86290-81-5 Index: 649-378-00-4	≥75 - ≤90	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]	H-P
tert-butyl methyl ether	REACH #: 01-2119452786-27 EC: 216-653-1 CAS: 1634-04-4 Index: 603-181-00-X	≥10 - ≤25	Flam. Liq. 2, H225 Skin Irrit. 2, H315	[1] [2]	-
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	<10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]	-
benzene	REACH #: 01-2119447106-44 EC: 200-753-7 CAS: 71-43-2 Index: 601-020-00-8	<1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304	[1] [2]	E
n-hexane	EC: 203-777-6 CAS: 110-54-3 Index: 601-037-00-0	<1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]	-

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Gasoline 98 (E5)

SECTION 4: First aid measures

Ingestion : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Extremely flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

SECTION 6: Accidental release measures

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not swallow. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Gasoline 98 (E5)

SECTION 7: Handling and storage

Category	Notification and MAPP threshold	Safety report threshold
P5a E2	10 tonne 200 tonne	50 tonne 500 tonne

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Gasoline	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2018). OEL, 8-h TWA: 240 mg/m ³ 8 hours. STEL, 15-min: 480 mg/m ³ 15 minutes.
tert-butyl methyl ether	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2018). STEL, 15-min: 360 mg/m ³ 15 minutes. OEL, 8-h TWA: 180 mg/m ³ 8 hours.
toluene	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2018). OEL, 8-h TWA: 150 mg/m ³ 8 hours. STEL, 15-min: 384 mg/m ³ 15 minutes.
benzene	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2018). Absorbed through skin. OEL, 8-h TWA: 0.7 mg/m ³ 8 hours.
n-hexane	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2018). OEL, 8-h TWA: 72 mg/m ³ 8 hours. STEL, 15-min: 144 mg/m ³ 15 minutes.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
tert-butyl methyl ether	DNEL	Long term Oral	7.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	53.6 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	178.5 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	214 mg/m ³	General population	Local
	DNEL	Short term Inhalation	357 mg/m ³	Workers	Local
	DNEL	Long term Dermal	3570 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5100 mg/kg bw/day	Workers	Systemic
toluene	DNEL	Long term Oral	8.13 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	56.5 mg/m ³	General population	Local
	DNEL	Long term Inhalation	56.5 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	192 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	192 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	226 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	226 mg/m ³	General population	Local
	DNEL	Short term Inhalation	226 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	384 mg/m ³	Workers	Local
n-hexane	DNEL	Short term Inhalation	384 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5.3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	16 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	75 mg/m ³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid. [Mobile liquid.]
- Appearance** : Clear.
- Color** : Colorless to light yellow.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : 7
- Melting point/freezing point** : <-50°C
- Initial boiling point and boiling range** : 25 to 220°C
- Flash point** : Closed cup: <-40°C [ASTM D56]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.

Gasoline 98 (E5)

Upper/lower flammability or explosive limits	: Lower: 1.4% Upper: 7.6%
Vapor pressure (37.8°C)	: 45 to 95 kPa
Vapor density	: >3 [Air = 1]
Density	: 0.75 g/cm ³ [15°C]
Solubility(ies)	: Insoluble in the following materials: cold water and hot water.
Dispersibility properties	: Not dispersible in the following materials: cold water and hot water.
Partition coefficient: n-octanol/ water	: 2 to 7
Auto-ignition temperature	: >250°C
Decomposition temperature	: >250°C
Viscosity (40°C)	: <1 cSt
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	LC50 Inhalation Vapor	Rat - Male, Female	>5610 mg/m ³	4 hours
tert-butyl methyl ether	LD50 Oral	Rat	13.6 g/kg	-
	LC50 Inhalation Gas.	Rat	23576 ppm	4 hours
	LC50 Inhalation Vapor	Rat	41000 mg/m ³	4 hours
toluene	LD50 Oral	Rat	4 g/kg	-
	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
benzene	LD50 Oral	Rat	636 mg/kg	-
	LD50 Oral	Rat	930 mg/kg	-
n-hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Gasoline 98 (E5)

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Gasoline	13600	N/A	N/A	N/A	N/A
tert-butyl methyl ether	4000	N/A	23576	41	N/A
toluene	N/A	N/A	N/A	49	N/A
n-hexane	15840	N/A	48000	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Gasoline	Skin - Edema	Rabbit	3	4 hours	72 hours
	Eyes - Edema of the conjunctivae	Rabbit	0.33	4 hours	72 hours
toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	870 ug	-
		Rabbit	-	24 hours 2	-
	Skin - Mild irritant	Pig	-	mg	-
			-	24 hours 250 UI	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
			-	mg	-
benzene	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Eyes - Moderate irritant	Rabbit	-	88 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2	-
			-	mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Mild irritant	Rabbit	-	24 hours 15	-
			-	mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
			-	mg	-
n-hexane	Eyes - Mild irritant	Rabbit	-	10 mg	-

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Gasoline	471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative
	475 Mammalian Bone Marrow Chromosomal Aberration Test	Experiment: In vivo Subject: Mammalian-Animal	Negative

Conclusion/Summary : Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	Positive - Dermal - TC	Mouse - Male	5 mg/kg	102 weeks; 3 days per week

Conclusion/Summary : Not available.

Reproductive toxicity

Gasoline 98 (E5)

SECTION 11: Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Gasoline	Negative	Negative	Negative	Rat - Male, Female	Inhalation: ≥ 20000 mg/m ³	7 weeks; 6 hours per day

Conclusion/Summary : Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	Negative - Inhalation	Rat	23900 mg/m ³	20 days; 6 hours per day

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Gasoline	Category 3	-	Narcotic effects
toluene	Category 3	-	Narcotic effects
n-hexane	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
toluene	Category 2	-	-
benzene	Category 1	-	-
n-hexane	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
Gasoline	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1
benzene	ASPIRATION HAZARD - Category 1
n-hexane	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Gasoline 98 (E5)

SECTION 11: Toxicological information

- Inhalation** : Adverse symptoms may include the following:
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 nausea or vomiting
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	Sub-acute NOEL Oral	Rat - Male	<500 mg/kg	28 days; 5 days per week
	Sub-acute NOAEL Dermal	Rat - Male, Female	375 mg/kg	28 days; 5 days per week
	Sub-chronic NOAEL Inhalation Vapor	Rat - Male, Female	10000 mg/m ³	90 days; 5 days per week

- Conclusion/Summary** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : May cause genetic defects.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
Gasoline	Acute EC50 3.7 mg/l Fresh water	Algae	96 hours	
	Acute EC50 4.5 mg/l Fresh water	Daphnia	48 hours	
	Acute LC50 10 mg/l Fresh water	Fish	96 hours	
	Chronic NOEC 2.6 mg/l Fresh water	Fish	14 days	
	tert-butyl methyl ether	Acute LC50 672000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
		Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	benzene	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
		Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
		Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
		Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
Acute EC50 29000 µg/l Fresh water		Algae - Pseudokirchneriella subcapitata	72 hours	
Acute EC50 1600000 µg/l Fresh water		Algae - Selenastrum sp.	96 hours	
Acute EC50 9.23 mg/l Fresh water		Daphnia - Daphnia magna - Neonate	48 hours	
Acute LC50 21 mg/l Marine water		Crustaceans - Artemia salina	48 hours	
n-hexane	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorboscha - Fry	96 hours	
	Chronic EC10 >1360 mg/l Fresh water	Algae - Scenedesmus subspicatus	96 hours	
	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days	
	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	4 weeks	

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Gasoline 98 (E5)	2 to 7	-	high
Gasoline	2 to 7	10 to 2500	high
tert-butyl methyl ether	1.04	1.5	low
toluene	2.73	90	low
benzene	2.13	11	low
n-hexane	4	501.187	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Gasoline 98 (E5)

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)





Waste code	Waste designation
13 07 02*	Gasoline

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1203	UN1203	UN1203	UN1203
14.2 UN proper shipping name	GASOLINE	GASOLINE	GASOLINE	Gasoline
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Hazard identification number 33

Limited quantity 1 L

Special provisions 534, 243, 363

Tunnel code (D/E)

SECTION 14: Transport information

- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤ 5 L or ≤ 5 kg.
Special provisions 243, 534, 363
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤ 5 L or ≤ 5 kg.
Emergency schedules F-E, S-E
Special provisions 243, 363
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.
Special provisions A100

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Ingredient name	Annex	Status
Benzene	Annex I - Part 1	Listed

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Gasoline 98 (E5)

SECTION 15: Regulatory information

Category

P5a
E2

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
Gasoline	Netherlands Carcinogenic Chemicals	(complexe) aardolie- en steenkoolderivaten EG nrs. beginnend met 232, 263, 265-275, 277, 278, 283-285, 287, 289, 291-298, 300, 302, 305-310	Carc.	Part of these derivates are only classified as carcinogenic if the content of benzene > 0.1% and/or benzo(a) pyrene > 0.005% or 1,3-butadiene > 0,1% or DMSO- extract > 3%. Please refer to Publicatieblad L381 of December 31th, 1994: the 21st amendment of Directive 67/548/EEC or later amendments of this Directive.
	Netherlands Mutagenic Substances	aardoliegasen en residuen EG nrs. beginnend met 232, 265-267, 268-273, 274, 277, 283-285, 287, 289, 292, 293, 295, 296, 298, 302, 305, 307, 308-310, 306	Muta.	
toluene	Netherlands Reprotoxic Chemicals	tolueen	Dev. development category 2	-
benzene	Netherlands Carcinogenic Chemicals	benzeen; benzol	Carc.	-
	Netherlands Mutagenic Substances	benzeen; benzol	Muta.	
n-hexane	Netherlands Reprotoxic Chemicals	n-hexaan	Repro. fertility category 2	-

Water Discharge Policy (ABM) : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

Hazard class for water (WGK) : 3

VOC content : VOC (w/w): 11.7%


International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

 Gasoline 98 (E5)

SECTION 15: Regulatory information

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals


Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: At least one component is not listed in DSL but all such components are listed in NDSL.
China	: Not determined.
Europe	: All components are listed or exempted.
Japan	: Japan inventory (ENCS) : Not determined. Japan inventory (ISHL) : Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: <input checked="" type="checkbox"/> All components are listed or exempted.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.


SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
 Am. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1A, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

Gasoline 98 (E5)

SECTION 16: Other information

H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1A	CARCINOGENICITY - Category 1A
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 1	FLAMMABLE LIQUIDS - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Muta. 1B	GERM CELL MUTAGENICITY - Category 1B
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 06-04-2020
Date of issue/ Date of revision	: 06-04-2020
Date of previous issue	: 18-10-2019
Version	: 1.05
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Product name : Gasoline 98 (E5)

Section 1 - Title

Short title of the exposure scenario : Distribution of Low Boiling Point Naphthas (Gasoline) - Classified as H340 and/or H350 and/or H361 (0 % - 1 % benzene) - Industrial

List of use descriptors : **Identified use name:** Distribution of substance
Process Category: PROC01, PROC02, PROC03, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC05, ERC06a, ERC06b, ERC06c, ERC06d, ERC07, ESVOC SPERC 1.1b.v1
Market sector by type of chemical product: PC13
Article category related to subsequent service life: Not applicable.

Processes and activities covered by the exposure scenario	: Bulk loading (including marine vessel/barge, rail/road car and IBC loading) of substance within closed or contained systems, including incidental exposures during its sampling, storage, unloading, maintenance and associated laboratory activities.
Additional information	: See section 3.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:	
Product characteristics	: Substance is complex UVCB.. Predominantly hydrophobic
Amounts used	: Fraction of EU tonnage used in region0.1 Regional use tonnage1.87E7 Fraction of regional tonnage used locally0.002 Annual site tonnage3.75E4 Maximum daily site tonnage1.2E5
Frequency and duration of use	: Continuous release Emission days300
Environment factors not influenced by risk management	: Local freshwater dilution factor10 Local marine water dilution factor100
Other conditions affecting environmental exposure	: Release fraction to air from process (initial release prior to RMM)0.001 Release fraction to wastewater from process (initial release prior to RMM)0.00001 Release fraction to soil from process (initial release prior to RMM)0.00001
Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation). If discharging to municipal sewage treatment plant, no on-site wastewater treatment required. Treat air emission to provide a typical removal efficiency of90 Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of12 If discharging to municipal sewage treatment plant, provide the required on-site wastewater removal efficiency of0
Organizational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Gasoline 98 (E5)

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via on-site sewage treatment 95.5 Total efficiency of removal from wastewater after on-site and off-site (municipal treatment plant) RMMs 95.5 Maximum allowable site tonnage (MSafe) 1.1E6 Assumed on-site sewage treatment plant flow 2000
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

General measures (skin irritants): Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

General measures (carcinogens): Consider technical advances and process upgrades (including automation) for the elimination of releases.

Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation.

Drain down systems and clear transfer lines prior to breaking containment.

Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks.

Regularly inspect, test and maintain all control measures.

Consider the need for risk-based health surveillance.

General exposures (closed systems) With sample collection: Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Wear suitable gloves tested to EN374.

General exposures (closed systems) Outdoor: Handle substance within a closed system.

Process sampling: Sample via a closed loop or other system to avoid exposure.

Laboratory activities: Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.

Bulk closed loading and unloading: Ensure material transfers are under containment or extract ventilation.

Equipment cleaning and maintenance: Drain down and flush system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Storage: Ensure operation is undertaken outdoors. Store substance within a closed system.

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100 %.

Physical state : Liquid, vapor pressure > 10 kPa at Standard Temperature and Pressure

Amounts used : Not applicable.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours

Human factors not influenced by risk management : Not applicable.

Other conditions affecting workers exposure : Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Hydrocarbon Block Method (Petrorisk)

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SPERC factsheet.

Health : Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Risk management measures are based on qualitative risk characterisation.

Annex to the extended Safety Data Sheet (eSDS)

Consumer

Identification of the substance or mixture

Product definition : Mixture
Product name : Gasoline 98 (E5)

Section 1 - Title

Short title of the exposure scenario : Use of Low Boiling Point Naphthas (Gasoline) as a Fuel - Classified as H340 and/or H350 and/or H361 (0 % - 1 % benzene) - Consumer
List of use descriptors : **Identified use name:** Use in fuel - Consumer
Substance supplied to that use in form of: As such
Sector of end use: SU21
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b, ESVOC SPERC 9.12c.v1
Market sector by type of chemical product: PC13
Article category related to subsequent service life: Not applicable.

Processes and activities covered by the exposure scenario : Covers consumer uses in liquid fuels.
Additional information : See section 3.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

Product characteristics : Substance is complex UVCB. Predominantly hydrophobic
Amounts used : Fraction of EU tonnage used in region 0.1
Regional use tonnage 1.39E7
Fraction of regional tonnage used locally 0.0005
Annual site tonnage 7.0E3
Maximum daily site tonnage 1.9E4
Frequency and duration of use : Continuous release
Emission days 365
Environment factors not influenced by risk management : Local freshwater dilution factor 10
Local marine water dilution factor 100
Other conditions affecting environmental exposure : Release fraction to air from wide dispersive use (regional only) Release fraction to air from process (initial release prior to RMM) 0.01
Release fraction to wastewater from wide dispersive use 0.00001
Release fraction to soil from wide dispersive use (regional only) 0.00001
Conditions and measures related to sewage treatment plant : Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).
Estimated substance removal from wastewater via on-site sewage treatment 95.5
Maximum allowable site tonnage (MSafe) 1.8E5
Assumed on-site sewage treatment plant flow 2000
Conditions and measures related to external treatment of waste for disposal : Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.
Conditions and measures related to external recovery of waste : This substance is consumed during use and no waste from the substance is generated.

Gasoline 98 (E5)

Contributing scenario controlling consumer exposure for 2:

Product categories [PC]: 13 - Fuels Liquid: automotive refuelling

Operations Conditions (consumer): Covers concentrations up to 1%. Covers use up to 52 days per year. Covers use up to 1 uses per day. Covers skin contact area up to 210.00 cm². For each use event, covers use amounts up to 37500 g. Covers outdoor use. Covers use in room size of 100 m³. For each use event, covers exposure up to 0.05 hours.

Risk management measures (RMM): No specific risk management measure identified beyond those operational conditions stated.

Product categories [PC]: 13 - Fuels Liquid: scooter refuelling

Operations Conditions (consumer): Covers concentrations up to 1%. Covers use up to 52 days per year. Covers use up to 1 uses per day. Covers skin contact area up to 210.00 cm². For each use event, covers use amounts up to 3750 g. Covers outdoor use. Covers use in room size of 100 m³. For each use event, covers exposure up to 0.03 hours.

Risk management measures (RMM): No specific risk management measure identified beyond those operational conditions stated.

Product categories [PC]: 13 - Liquid: garden equipment - use

Operations Conditions (consumer): Covers concentrations up to 1%. Covers use up to 26 days per year. Covers use up to 1 uses per day. For each use event, covers use amounts up to 750 g. Covers outdoor use. Covers use in room size of 100 m³. For each use event, covers exposure up to 2.00 hours.

Risk management measures (RMM): No specific risk management measure identified beyond those operational conditions stated.

Product categories [PC]: 13 - Liquid: garden equipment - refuelling

Operations Conditions (consumer): Covers concentrations up to 1%. Covers use up to 26 days per year. Covers use up to 1 uses per day. Covers skin contact area up to 420.00 cm². For each use event, covers use amounts up to 750 g. Covers use in a one car garage (34 m³) under typical ventilation. Covers use in room size of 34 m³. For each use event, covers exposure up to 0.03 hours.

Risk management measures (RMM): No specific risk management measure identified beyond those operational conditions stated.

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100 %.

Physical state : Liquid, vapor pressure > 10 kPa at Standard Temperature and Pressure

Amounts used : For each use event, covers use amounts up to 37500 g. Covers skin contact area up to 420 cm².

Frequency and duration of use/exposure : Covers use up to 0.143 uses per day. For each use event, covers exposure up to 2 hours.

Other given operational conditions affecting consumers exposure : Unless otherwise stated, Covers use at ambient temperatures. Covers use in room size of 20 m³. Covers use under typical household ventilation.

Conditions and measures related to personal protection and hygiene

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Hydrocarbon Block Method (Petrorisk)

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Consumers: 2:

Exposure assessment (human): : ECETOC TRA consumer v3

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment

: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

Health

: Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.